

## RW 642 LIQUID RIGWASH

### GENERAL DESCRIPTION

Norchem RW 642 Liquid Rigwash is a heavy duty biodegradable cleaner and degreaser containing a complex blend of highly active surfactants and emulsifiers.

### ADVANTAGES:

- Fast penetration and soil removal
- Readily saponifies and emulsifies off contaminations, resulting in an easily rinsed out mixture
- Out-performing any soap-based detergents
- Non-flammable, no objectionable odour and non-corrosive
- Biodegradable, superior detergency and free rinsing

### APPLICATION:

RW 642 is mainly used as a liquid 'rigwash' and high pressure/steam cleaner to remove oily and greasy contamination from heavy soiled rigs, hoists, cranes, derricks, bulkheads, deck areas, galley equipments etc.

### USE DIRECTIONS:

1. Rigwash  
Depending on the severity of contamination, dilute one litre of RW 642 with 10 to 15 parts water. Apply the mixture on surfaces to be cleaned by pressure jet, brush or swap with a mop. Allow 20 to 30 minutes for RW 642 to penetrate and dissolve the greasy or oily surfaces. Rebrush before rinsing off with clean water.
2. High Pressure/Steam Cleaning  
Depending on the degree of contaminated soils, mix one litre of RW 642 with 10 litres of water and charge solution into the stock tanks.

### PRODUCT SPECIFICATIONS:

Appearance : Clear Liquid  
Flash Point : None  
Boiling Point : 100 °C  
Pour Point : -6 °C  
Stability : Indefinite when stored frost free

### PRECAUTIONS

Avoid contact. In case of contact with skin or eyes, flush with copious amount of water. Seek medical attention if condition does not improve. Rubber gloves and goggles are to be worn. Harmful if swallowed.

### PACKAGE

Supplied in 25 or 200 litres container and 1000 litres IBC tank.