

Ultra-Spill Berms®



Temporary berm seals off spills from the environment, nearby drains, and doorways

- + Standard 10-foot sections can be cut to various lengths.
- + Unique, urethane material “weeps” into small cracks and crevices to seal off liquid flow.
- + Spill Berm is non-absorbing and is easily cleaned for repeated use.
- + Applications include:
 - Spill response
 - Temporary secondary containment
 - Sealing off of doorways during wash down operations
- + Flexible Ultra-Spill Berm will bend and turn to form almost any shape while temporarily “bonding” to any smooth surface.
- + Helps comply with NPDES and SPCC.



2104: Optional carrying case


Patents: See www.ultratechpatents.com

Part#	Color	Dimensions	Weight lbs. (kg)
2100	Orange	10' x 4" x 2 1/4" (3,048 mm x 102 mm x 58 mm)	31.0 (14.0)
2050	Black	10' x 4" x 2 1/4" (3,048 mm x 102 mm x 58 mm)	31.0 (14.0)

2101 Connectors used to connect 10' sections · 2102 90° Corners used with Connectors · 2104 Carrying case

2101: Black Connector

2102: 90° Orange Corner



Decide what shape or configuration is required and use optional Connectors and 90° Corners to complete the area.

Ultra-Spill Berm Plus Model®



Taller spill berm helps contain or divert larger volume spills

- + Flexible polyurethane construction is non-absorbent and chemical resistant — easily cleans with soap and water for repeated uses.
- + Built-in connectors allow multiple 5-foot units to be quickly and easily connected.
- + Helps comply with NPDES and SPCC.



Patents: See www.ultratechpatents.com

Part#	Dimensions	Weight lbs. (kg)
2054	5' x 4" x 4 1/2" (1,524 mm x 102 mm x 114 mm)	16.0 (7.0)

