## Ultra-IBC Hard Top® (SPCC)











## Comply with regulations while storing IBC tanks outdoors

- + Upper roll-top door and lower swing-out doors combine to allow easy and convenient access to IBC.
- + Large storage area (52" x 52" x 61") accommodates most IBCs, totes and tanks.
- + Low profile (28" height), 365-gallon containment sump allows safe material handling and dispensing.
- + Forkliftable, lockable, all-polyethylene design will not rust or corrode.
- + Helps meet Stormwater Management Regulations — NPDES, 40 CFR 122.26 (1999).
- + Meets SPCC and EPA Container Storage Regulation 40 CFR 264.175.





1162

Part#	Description	<b>Dimensions</b> in. (mm)	<b>Uniformly Dist. Load</b> lbs. (kg)	<b>Containment Cap.</b> gal. (L)	<b>Weight</b> lbs. (kg)
1162	IBC Hard Top Without Drain	64½ x 62 x 96 (1,639 x 1,575 x 2,439)	8,500 (3,856)	365 (1,382)	525.0 (239.0)
1161	IBC Hard Top With Drain	64½ x 62 x 96 (1.639 x 1.575 x 2.439)	8.500 (3.856)	365 (1.382)	525.0 (239.0)

## Outdoor storage for two IBC tanks

Ultra-Twin IBC Hard Top® 🗫

- + Unique, lockable, dual closure allows quick access to tanks.
- + Roll-top covers can be easily lifted for routine visual inspection.
- + Swing-out doors provide safety and convenience for loading/unloading tanks.
- + Large storage area (52" x 52" x 61") accommodates most IBCs, totes and tanks. (All materials stored must be chemically compatible.)
- + Meets Stormwater, SPCC and, EPA Container Storage Regulation 40 CFR 264.175.



Part#	Description	Dimensions in. (mm)	Weight Capacity lbs. (kg)	Containment Capacity gal. (L)	<b>Weight</b> lbs. (kg)
1148	Twin IBC Hard Top Without Drain	128 x 67 x 96 (3,251 x 1,702 x 2,438)	8,000 (3,629) UDL/side	535 (2,025)	1,067.0 (484.0)
1149	Twin IBC Hard Top With Drain	128 x 67 x 96 (3,251 x 1,702 x 2,438)	8,000 (3,629) UDL/side	535 (2,025)	1,067.0 (484.0)
1160	Bucket Shelf	19½ x 16 x 14½ (495 x 406 x 368)	-	-	10.0 (5.0)