

S/N	PRODUCT CODE	DESCRIPTION	BENEFITS	APPLICATION	COLOUR
1.	Lithium MP Grease No.2	Norchem MP is a Lithium-Based NLGI 2 grease. It serves all of the areas where extreme in temperature and corrosion are not critical. Also available in NLGI 1.	 Contains heat-stable, anti-wear and antioxidant additives. Excellent structural stability. Good resistance to water washout Lead, chlorine and nitrite free Great pumpability for easy use. 	 Wheel, plain and antification bearings. Universal ball joints. Pumps, screws, shears, presses, etc. All mobile equipment operating under moderate conditions. 	
2.	Multilube EP Greases	Norchem EP Greases are Lithium-12 Hydroxy stearate-based grease with extreme pressure, anti-wear and shear stability. Specially suitable for vigorous and heavy-duty applications. Operating temperature range of - 20°C to + 120°C. Also available in NLGI 1, 2 and 3.	 Superior lubrication under severe conditions. Stays in place in extreme environments to protect equipment. Suitable for low and high temperature applications. Protection against rust and corrosion. Extend bearing life in wet conditions. Lead, chlorine and nitrite free. 	 Recommended where high or shock loads are present or where vibration is a problem. Anti-friction and plain bearings. Pumps, brushings, motors, joints, rollers. All industrial, automotive and marine applications. 	
3.	750 Lithium Complex EP Grease	Norchem 750 is a lithium complex NLGI 2 grease containing highly refined base oils and additives to meet severe requirements of equipment and machinery. Product is smooth, somewhat tacky and slightly stringy.	 Excellent lubricity and good resistance to abrasion and extreme pressure. Good anti-wear and anti-rust properties. Resists thinning or hardening in bearings, minimizing leakage and maintaining extended life service. Wide temperature range of - 20°C to + 180°C. Superior water resistance. 	 Recommended for use on all types of bearings. Universal joints, chassis, fifth wheels, disc brakes and other applications. Use as a heavy-duty grease in automotive, trucks, buses, farm and marine equipment. Robust grease for a wide range of marine and industrial applications. 	



4.	WG 758 Wire Rope Grease	Norchem WG 758 is a mineral lithium soap grease. Product contains good refined oil, thickener, adhesion and wetting agents.	 Possess excellent adhesion and lubricating properties. Protects against the corrosion effect of salt or fresh water. Excellent mechanical and oxidation stability (- 20°C to + 120°C) 	 All types of new or old wire ropes. Anchor chains, open gears, moist cables, lifeboat davits, etc. Fittings, shackles, wheel axles. As a general-purpose grease. 	
5.	OGL 759 Wire Rope & Open Gear Lubricant	Norchem OGL 759 is a lithium soap thickened gear and wire rope lubricant. Contains various refined petroleum additives rather than asphalt to ensure excellent oxidation and anti-rust resistance.	 Highly tacky and adhesive. Excellent lubrication under heavy loaded gears and wire ropes. Good penetration into strands and core of wire ropes. Superior protection against water contact. 	 All types of wire ropes and open gears operating under slow speeds. Cables, derricks and anchor chains. Recommended for application of railways, locomotive friction motor gear. 	
6.	761 HD Wire & Open Gear Grease	Norchem 761 is a premium grade environmentally friendly calcium sulfonate heavy-duty wire and open gear grease. Product contains a variety of additives such as thickener, adhesive agent and corrosion inhibitors.	 Designed to be used in harsh and wet environments. Protects against the corrosion effect of either salt or fresh water. Excellent adhesion and super tacky. Extraordinary performer at high and low temperature. Lengthens service life of wire ropes, open gears and equipment. 	 Lubrication and protection of all kinds of wire ropes, open gears, anchor chains, etc. Long-term protection of metal cables against rust and corrosion. As a heavy-duty grease for the marine, offshore, refineries and other industrial applications. 	
7.	762 Calcium Sulfonate HD Grease	Norchem 762 is a premium grade environmentally friendly heavy-duty grease manufactured from highly refined mineral oils with the combination of EP/AW additives.	 Excellent performance under heavy load. Superior protection under both shock loading and running conditions. Wide operating temperature range - 20°C to + 180°C. Super tacky and does not drip out under running conditions. 	 Recommended for marine, loggings and oilfield applications. All types of bearings and equipment. As a heavy-duty multipurpose grease. 	