

SC 233 SEPARATOR CLEANER

APPLICATION

Cleaning of fuel and lube oil separator discs contaminated by oily sludge and water. Also very well suited for removal of oil and water formed, hard deposits on separator discs.

USE DIRECTIONS

Use neat or dilute with 1 part to 4 parts of water depending on the degree of contamination.

Cleaning time will vary from 30 minutes to 3 hours depending on the severity of contaminated soil. When disc has been cleaned, it should be rinsed thoroughly with copious amount of water.

For best result, heat the solution up to 50°C to accelerate the process.

CAUTION : *Not to be used on galvanized or tinned surfaces.*

PRODUCT SPECIFICATION

Solution consisting of phosphoric acid, aliphatic solvents, wetting and penetrating agents.

Appearance	: Clear liquid
Boiling Point	: 102°C (215.6°F)
Freezing Point	: 1°C (33.8°F)
Flash Point	: None
Density	: 1.176 ± 0.02
pH	: Approx. 1.0
Stability	: Indefinite

PRECAUTIONS

Wear goggles and gloves when using SC 233. Wash with plenty of water if splashes on skin or eyes and seek medical attention. Avoid vapor when liquid is heated. Harmful if swallowed.

PACKAGE

Supplied in 25 litres container.